

Technotes

Highlighting technical features for
Thermo Scientific Vacutherm Vacuum Ovens

Key Features

- Three chamber sizes available: 25L, 53L, 128L
- Outstanding capabilities for fast and gentle drying
- Customizable options available to fit your application needs

Why choose a Vacutherm vacuum oven for your lab?

Dry up to six times faster than conventional units with a Thermo Scientific™ Vacutherm™ vacuum heating and drying oven.* Minimize operation time with outstanding heat transfer and fast heat up.**



MODELS

- Jacket-heated models, available with Kelvitron™ microprocessor control, operate up to 200°C
- Shelf heated models operate up to 300°C (400°C option offered), available with Digicon multi-channel controls which allow you to manage each shelf temperature separately

TYPICAL APPLICATIONS

Food industry

- Determination of the solid content of foods. Samples are typically dried under vacuum at around 60°C

~ **Our Solution:** Vacutherm VT6060 M or VT6130 M oven with standard pump and trap

Pharmaceutical industry

- Drying additives for pharmaceuticals. Samples are dried with pressure at 10-1mbar or forming gas at 60–80°C.

~ **Our Solution:** Vacutherm VT6060 P or VT6130 P oven with an oil-free pump

- Gentle drying of raw materials and determination of solid content. Samples are dried under vacuum at 60–80°C.

~ **Our Solution:** Vacutherm VT6060 M or VT6130 M oven with standard pump and trap

* Based on internal testing

** Based on previous models

Specifications and Ordering Information

Cat.No.	Model	Type	Capacity	Interior Dimensions W x H x D	Exterior Dimensions ¹ W x H x D	Rated Temp. ^{2,3}	Spatial temp. deviation ^{2,4}	Heat Output (at max. temp.)	Electrical ⁵	Weight
51014550	VT 6025	Jacket-heated no inert gas connection	25L (0.88 cu.ft.)	300 x 275 x 307mm (11.8 x 10.8 x 12.1in.)	480 x 600 x 450 mm (18.9 x 23.6 x 17.7in.)	200°C	±4 (@200°C)	340 Wh/h	230V 50/60Hz, 1.3kW	58kg (128 lb.)
51014552	VT 6025	Jacket-heated	25L (0.88 cu.ft.)	300 x 275 x 307mm (11.8 x 10.8 x 12.1in.)	480 x 600 x 450 mm (18.9 x 23.6 x 17.7in.)	200°C	±4 (@200°C)	340 Wh/h	230V 50/60Hz, 1.3kW	58kg (128 lb.)
51014553	VT 6025	Jacket-heated ⁶	25L (0.88 cu.ft.)	300 x 275 x 307mm (11.8 x 10.8 x 12.1in.)	480 x 600 x 450 mm (18.9 x 23.6 x 17.7in.)	200°C	±4 (@200°C)	340 Wh/h	230V 50/60Hz, 1.3kW	58kg (128 lb.)
51014554	VT 6025	Jacket-heated with Digicon S ⁷	25L (0.88 cu.ft.)	300 x 275 x 307mm (11.8 x 10.8 x 12.1in.)	480 x 600 x 450 mm (18.9 x 23.6 x 17.7in.)	200°C	±4 (@200°C)	340 Wh/h	230V 50/60Hz, 1.3kW	58kg (128 lb.)
51014539	VT 6060 M	Jacket-heated	53L (1.87 cu.ft.)	415 x 345 x 371 mm (16.3 x 13.6 x 14.6in.)	744 x 576 x 570 mm (29.3 x 22.7 x 22.4in.)	200°C	±4 (@200°C)	540Wh/h	230V 50/60Hz, 1.7kW	82kg (181 lb.)
51014542	VT 6060 P	Shelf-heated ⁸	53L (1.87 cu.ft.)	415 x 345 x 371 mm (16.3 x 13.6 x 14.6in.)	744 x 576 x 570 mm (29.3 x 22.7 x 22.4in.)	300/400°C	±3 (@200°C) ±7 (@300°C) ±9 (@400°C)	450 Wh/h	230V 50/60Hz, 1.6kW	90kg (198 lb.)
51014541	VT 6130 M	Jacket-heated	128L (4.52 cu.ft.)	495 x 489 x 529 (19.5 x 19.3 x 20.8in.)	895 x 720 x 750 mm (35.2 x 28.3 x 29.5in.)	200°C	±7 (@200°C)	870 Wh/h	230V 50/60Hz, 2.2kW	153kg (337 lb.)
51014543	VT 6130 P	Shelf-heated ⁸	128L (4.52 cu.ft.)	495 x 489 x 529 mm (19.5 x 19.3 x 20.8in.)	895 x 720 x 750 mm (35.2 x 28.3 x 29.5in.)	300/400°C	±4 (@200°C) ±7 (@300°C) ±9 (@400°C)	880 Wh/h	230V 50/60Hz, 3.0kW	164kg (362 lb.)

¹ Depth without handle and wall distance. Dimensions: handle 70 mm, wall distance 80 mm

² The values stated apply to the empty oven and vacuum operation in acc. with DIN 12880, part 2

³ Control range M: electronic controller from TA + 15°C; control range P: electronic controller from TA + 10°C; TA = Ambient temperature

⁴ Measured on the shelves

⁵ Other voltages on request

⁶ With digital pressure display and recorder output

⁷ Digicon S: analog temperature controller

⁸ Comes standard with Digicon multi-channel controller and rated temperature of 300°C; for 400°C: order option in addition, see next page

Thermo
SCIENTIFIC

Find the right Vacuotherm vacuum oven for your application needs



- Gentle drying of heat sensitive materials
- Significantly reduced drying times when compared to convectional oven without vacuum
- Drying of intricately designed parts
- Elimination of oxidation associated with heat treatment
- Targeted recovery of degassed products

DIAPHRAGM PUMPS					ROTARY VANE PUMPS
Vacuum Pumps		MD 12H	HMD 4C	HMZ 2C	RE 9H
Cat. No.		50040078	50028362	50028364	50028361
Rated pumping capacity (Pneurop)	m ₃ /h	9.6	3.0	1.7	8.6
Total final pressure without gas ballast	mbar	2	2	10	0.1
Total final pressure with gas ballast	mbar	<10	<10	<20	6 x 10 ⁻¹
Water vapor compatibility	mbar	–	–	–	40
Capacity of trap	ml	725	500	500	500
Weight	kg	24	18	14	21.6
Dimensions with trap (w/h/d)	mm	240 x 300 x 610	241 x 500 x 338	241 x 326 x 336	260 x 232 x 460
Vacucenter with pump		MD 12H	HMD 4C		RE 9H
Cat. No.*		50044332	50044333	–	50044334
Voltage	V3N~, 50/60 Hz	400	400	–	400
Max. rated power	kW	3.37	3.2	–	3.37
External dimensions (W x H x D)	mm	895 x 650 x 900	895 x 650 x 900	–	895 x 650 x 900
Total weight	kg	88	80	–	86
Protection class		I	I	–	I
Protection type		IP 20	IP 20	–	IP 20

*In combination with VT 6060 or VT 6130

ACCESSORIES	
Cat.No.	Description
50028403	Additional shelf for VT6025 (incl. shelf supports)
50043975	Additional shelf for VT6060 M (incl. shelf supports)
50043976	Additional shelf for VT6130 M (incl. shelf supports)
50048621	Stainless steel tray for VT6060
50048619	Stainless steel tray for VT6130
50048620	Aluminum tray for VT6060 M/P
50048618	Aluminum tray for VT6130 M/P
50046860	Stainless steel vacuum connection kit for tubing, 10mm diameter (all models)
50029890	Support frame, 780 mm height, for VT6060 M/P
50029597	Support frame, 780 mm height, for VT6130 M/P
FACTORY INSTALLED OPTIONS	
Cat.No.	Options for Vacuotherm 6060 and 6130 M/P
51900284	RS 232 computer interface for Kelvicon controller
51900069	Digital pressure display
51900193	Pressure controller with solenoid valve
51900071	VITON door gasket for VT 6060 M
51900072	VITON door gasket for VT 6130 M
51900205	Daily program timer, mechanical
51900073	24 hour timer (20 h at 60 Hz)
51900008	Weekly program timer, mechanical
51900161	Weekly program timer, digital
51900074	Digital sample temperature display with flexible pt 100 temperature sensor and socket for external data recorder
51900209	Thermicon P temperature program controller (M-models only)
51900297	Eurotherm 2404/P4 temperature controller with RS232 interface (M-models only)
51900298	Eurotherm 2404/P4 temperature controller with RS 422/485 interface (M-models only)
51900081	Central monitoring connection
Cat.No.	DigiCon® S temperature controller with analog interface 0–20 mA/0–10 V
51900194	(200 °C): VT 6060 M and VT 6130 M
51900195	(300 °C): VT 6060 P and VT 6130 P
51900196	(400 °C): VT 6060 P
51900197	(400 °C): VT 6130 P
Cat.No.	Rated temperature of 400 °C, (door without inspection window)
51900079	for VT 6060 P
51900080	for VT 6130 P
Cat. No.	Vacuum chamber with rounded corners at the rear
51900075	for VT 6060 M
51900077	for VT 6060 P
51900076	for VT 6130 M
51900078	for VT 6130 P
Cat. No.	Options for Vacuotherm 6025
51900326	Precision control valve for standard model (order nos. 51014550 and 51014551 only)
51900284	RS232 computer interface

thermoscientific.com/vacuumovens

© 2014 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

Australia +61 39757 4300
Austria +43 1 801 40 0
Belgium +32 53 73 42 41
China +800 810 5118 or
 +400 650 5118
France +33 2 2803 2180
Germany national toll free 0800 1 536 376
Germany international +49 6184 90 6000

India toll free 1800 22 8374
India +91 22 6716 2200
Italy +39 02 95059 552
Japan +81 3 5826 1616
Netherlands +31 76 579 55 55
New Zealand +64 9 980 6700
Nordic/Baltic/CIS countries
 +358 9 3291 0200

Russia +7 812 703 42 15
Spain/Portugal +34 93 223 09 18
Switzerland +41 44 454 12 22
UK/Ireland +44 870 609 9203
USA/Canada +1 866 984 3766

Other Asian countries +852 2885 4613
Countries not listed +49 6184 90 6000

Thermo
 SCIENTIFIC
 A Thermo Fisher Scientific Brand